

# SEPARATOR FOR BATTERY AND ITS MANUFACTURING METHOD AND BATTERY

**Patent number:** JP2001307710  
**Publication date:** 2001-11-02  
**Inventor:** YAMAMOTO HIROYUKI; SANO TOYOHICO; HORI SHUJI; TANAKA TOMOFUMI; KIDA TATSUNOBU  
**Applicant:** DAIWA SPINNING CO LTD  
**Classification:**  
**- international:** H01M2/16; H01M10/30  
**- european:**  
**Application number:** JP20000116888 20000418  
**Priority number(s):** JP20000116888 20000418

[Report a data error here](#)

## Abstract of JP2001307710

**PROBLEM TO BE SOLVED:** To provide a battery separator, which has a bonding strength and a hydrophilicity, and which can be highly sulfonated in loose sulfonation processing conditions, and in which a battery capacity is improved without reducing a battery life, and to provide a battery with a battery separator incorporated. **SOLUTION:** A nonwoven fabric, which is composed of at least 5 mass % of a synthetic fiber A made by exposing a polymerized polyethylene using a metallocene catalyst (MPE) on at least a part of a fiber surface and at least 5 mass % of a synthetic fiber B made by exposing a high density polyethylene on at least a part of a fiber surface, is manufactured. A thermal bonding using MPE component is performed entirely and a sulfonation is performed to give it a hydrophilicity to make it a battery separator.

---

Data supplied from the *esp@cenet* database - Worldwide